

Product Number: FSU120

SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifiers

Product Name: METHYL ETHYL KETONE

Product Number: FSU120

Recommended Use of the chemical and restrictions on use: Use as a thinning solvent

Company Details

AUSTRALIAN SPECIALTY INKS PTY LTD A.B.N. 71 002 591 620 17 REAGHS FARM ROAD MINTO NSW 2566 (02) 9603-3399 A/H (02) 9792-7790 or mobile 0414 616247 Email: <u>info@austspecialtyinks.com.au</u> Website: www.austspecialtyinks.com.au

Emergency Telephone Number

Mob: 0414616247

2. HAZARDS IDENTIFICATION

Classified as hazardous according to the Globally Harmonised System of Classification and labeling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th Edition).

Signal Words: Flammable Liquids: Category 2 DANGER

Poisons Schedule: 5



17 Reaghs Farm Rd, Minto NSW 2566 Telephone: (02) 9603-3399 Fax: (02) 9603-7761 Website: www.austspecialtyinks.com.au

Product Number: FSU120

GHS Classification	Pictogram	Hazard Statement
Flammable Liquids, Category 2		H225 Highly Flammable liquid and vapour.
Acute Toxicity - Inhalation – Category 4 Eye Irritation – Category 2A Skin Corrosion/Irritation – Category 2		H336 May cause drowsiness or dizziness H320 Causes eye irritation AUH066 Repeated exposure may cause skin dryness and cracking.

Precautionary statements:

GENERAL	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
PREVENTATIVE	
P201 P202	Obtain special instructions before use Do not handle until all safety precautions have been read and understood
P202 P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking
P233	Keep container tightly closed
P240	Ground/Bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing fume/mist/vapours/spray
P271 P273	Use only outdoors or in a well-ventilated area Avoid release to the environment
P273	Wear protective gloves/eye protection/face protection
P281	Use personal protective equipment as required
RESPONSE	
P301+P310	If SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353	ON SKIN (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P303+P361+P353	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if
	present and easy to do - continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P331	Do NOT induce vomiting
D070, D070	In each of fire Line and earth from dry chemical or earbon diavide for extinction
P370+P378 P391	In case of fire: Use sand, earth, foam, dry chemical or carbon dioxide for extinction Collect spillage
1001	
STORAGE	
P403+P235	Store in a well ventilated place. Keep cool
P405	Store locked up



17 Reaghs Farm Rd, Minto NSW 2566 Telephone: (02) 9603-3399 Fax: (02) 9603-7761 Website: www.austspecialtyinks.com.au

Product Number: FSU120

DISPOSAL

P501 Dispose of contents/container in accordance with local regulations

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients Names and Proportions

Chemical entity	CAS Number	Proportion
2-Butanone	108-94-1	100%

4. FIRST-AID MEASURES

Description of necessary first aid measures

Inhalation:	Remove victim from exposure if safe to do so. Administer artificial respiration if breathing is stopped. Keep at rest. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. If irritation occurs seek medical advice.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.
Ingestion:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Symptoms caused by exposure

Inhalation:	Breathing of high vapour concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Skin Contact:	May include burning sensation, redness, swelling and/or dried cracked appearance.
Eye Contact:	Will include burning sensation, redness, swelling and/or blurred vision. Can cause corneal burns.
Ingestion:	May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever. Irritation of the gastrointestinal tract.



Product Number: FSU120

Medical attention and special treatment: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing equipment

Alcohol stable foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet.

Specific hazards arising from the chemical

Carbon monoxide and/or carbon dioxide may be evolved. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

Special protective equipment and precautions for fire fighters

Wear liquid-tight chemical protective clothing and self-contained breathing apparatus. Hazchem code is •2YE.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Environmental precautions

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

For small spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.



Product Number: FSU120

7. HANDLING AND STORAGE

Precautions for safe handling

Flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.

Conditions for safe storage, including any incompatibilities

Bulk storage tanks should be bunded. Store in a well ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidizers and alkalis. Do not pressurize, cut, heat or weld containers – residual vapours are flammable. This product is flammable and will fuel a fire in progress. Avoid prolonged contact with natural, butyl or nitrile rubbers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure control measures

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia – FSU120: 445 mg/m³ (150ppm) TWA (8hr). Short term exposure limit (STEL) is 890 mg/m³ (300ppm), which is the maximum allowable exposure concentration at any time.

Biological monitoring

Not available.

Engineering controls

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.



17 Reaghs Farm Rd, Minto NSW 2566 Telephone: (02) 9603-3399 Fax: (02) 9603-7761 Website: www.austspecialtyinks.com.au

Product Number: FSU120

Individual protection measures

Eye and face protection:	Wear safety goggles.
Skin protection:	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.
Respiratory Protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65° C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colourless clear liquid
Odour threshold (ppm):	Data not available
Percent Volatiles:	100
Initial boiling point and boiling range (⁰ C):	78 - 81
Flash point (⁰ C):	-4 (closed cup)
Evaporation rate (Butyl acetate = 1):	Data not available
Flammability:	Flammable
Upper/lower flammability or explosive limits (%):	1.8 – 11.5
Vapour pressure (@ 20⁰C):	9.3
Vapour density (air = 1):	>1.00



17 Reaghs Farm Rd, Minto NSW 2566 Telephone: (02) 9603-3399 Fax: (02) 9603-7761 Website: www.austspecialtyinks.com.au

Product Number: FSU120

Density (g/ml @ 15⁰C):	.81
Solubility:	Completely miscible with water
Partition coefficient n-octanol/water:	Data not available
Auto-ignition temperature (⁰ C):	>450
Decomposition temperature (⁰ C):	Data not available
Kinematic viscosity (mm ² /s @ 20 ⁰ C):	Data not available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions of use.

Chemical stability

Stable under normal conditions of use.

Possibility of hazardous reactions

Oxidising agents, mineral acids, halaogenated organic compounds, chloroform and alkalis, stored mixtures with IPA.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials

Reacts violently with strong oxidizing agents, nitric acid and sulphuric acid. Natural rubber, butyl rubber, EPDM and polystryrene.



Product Number: FSU120

Hazardous decomposition products

Burning can produce carbon monoxide and/or carbon dioxide. A complex mixture of airborne solids, liquids, gases and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	LD50 Oral (rat): 2737mg/kg Dermal TC _{Lo} : MEK: 100ppm (inhalation, human)
Skin corrosion/irritation:	Prolonged contact may cause defatting of skin which can lead to dermatitis. Can be absorbed through skin with resultant adverse effects.
Serious eye damage/irritation:	Irritating to eyes, will cause redness and swelling with a burning sensation and blurred vision. Can cause corneal burns.
Germ cell mutagenicity:	Not mutagenic.
Carcinogenicity:	Not applicable.
Reproductive toxicity:	Not expected to affect reproduction.
Specific Target Organ Toxicity (STOT) – single exposure:	Breathing in vapour may produce respiratory irritation. In high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgment and if exposure is prolonged unconsciousness.
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system. Prolonged exposure can cause dermatitis.
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.



Product Number: FSU120

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute toxicity

Fish:	LC ₅₀ (96hr): Goldfish: 2400000µg/l
Aquatic invertebrate:	LC₅₀(24hr): Daphnia Magna: 520000µg/l
Algae:	LO _{EC} : Blue-green algae: 120000µg/l (Threshold 7-8 days)
Microorganisms:	LO _{EC} : Green algae: 4300000µg/l (Threshold 7-8 days)

Persistence and degradability

Expected to be readily biodegradable. Volatises in air.

Bioaccumulative potential

Has the potential to bioaccumulate.

Mobility in soil

This product is highly volatile and will rapidly evaporate to the air if released into the water.

Other adverse effects

Data not available.



Product Number: FSU120

13. DISPOSAL CONSIDERATIONS

Ensure waste disposal conforms to local waste disposal regulations. Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities.

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

14. TRANSPORT INFORMATION

UN number:	1193
Proper shipping name:	Methyl Ethyl Ketone
Australian Dangerous Goods class:	3
Australian Dangerous Goods packing group:	11
Hazchem code:	•2YE

15. REGULATORY INFORMATION

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5
Australian Inventory of Chemical Substances (AICS):	Listed
Australian Dangerous Goods class:	3
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ):	HB76
Hazchem code:	•2YE



17 Reaghs Farm Rd, Minto NSW 2566 Telephone: (02) 9603-3399 Fax: (02) 9603-7761 Website: www.austspecialtyinks.com.au

Product Number: FSU120

16. ANY OTHER RELEVANT INFORMATION

Date of preparation:	15/04/2019
Revision number:	1
Changes in this revision:	Update to GHS SDS standard