



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ENAMEL THINNERS F59-180

Page 1 of 4

MATERIAL SAFETY DATA SHEET

Classified as hazardous according to criteria of Worksafe Australia.

Date of issue: March 2009

COMPANY DETAILS

AUSTRALIAN SPECIALTY INKS PTY LTD
A.B.N. 71 002 591 620
17 REAGHS FARM ROAD MINTO NSW
2566 (02) 9603-3399
A/H (02) 979-27790 or mobile 0414 616247

IDENTIFICATION

Product Name: ENAMEL THINNERS F59-180
U.N. Number: 1300
Trade Name:
Other Names:
Class: 3
Hazchem Code: 3[Y]
Manufacturers Code: F59-180
Poisons Schedule: S5
Use: Product is for use as a solvent.

Physical Description/Properties:

Appearance: Colourless mobile liquid, aromatic hydrocarbon odour.
Density: 0.81
Boiling Point/Range: 149°C-196°C
Vapour Pressure: 0.8kPa @ 38°C
Percent Volatiles: 100
Flash Point: 37°C (TCC)
Flammability Limits(%): LEL:1.0 UEL:7.5
Solubility in water: < 0.1% @ 20°C

Ingredients

Chemical entity	CAS No.	Proportion
Liquid hydrocarbons	64742-95-6	MED(98-100%)



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ENAMEL THINNERS F59-180

Page 2 of 4

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed: May cause irritation to mouth, throat and digestive tract. Swallowing can result in drowsiness, nausea, vomiting and may lead to unconsciousness. Aspiration during swallowing or vomiting may cause bronchopneumonia or pulmonary oedema.

Eye: Liquid or vapour may cause eye irritation but will not damage eye tissue.

Skin: May cause skin irritation after prolonged or repeated contact.

Inhaled: High vapour concentrations may cause irritation to mucous membranes and the respiratory tract. Prolonged exposure to vapours can effect the central nervous system and result in headaches and dizziness or unconsciousness.

Chronic: Repeated or prolonged skin exposures may produce pronounced irritation and dermatitis.

FIRST AID

Swallowed: Wash out mouth with water. Do not induce vomiting. Give water to drink. Keep warm and at rest. Obtain medical advice urgently.

Eye: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical advice urgently.

Skin: Immediately flood the skin with large quantities of water for at least 15 minutes, preferably under a shower. Remove contaminated clothing as washing proceeds. Continue washing for at least 10 minutes. Contaminated clothing should be washed or dry-cleaned before re-use. Dispose of boots contaminated internally.

Inhaled: Remove from exposure. Keep warm and at rest. Seek medical attention. If breathing stops or shows signs of failing give artificial respiration. If heartbeat absent, give external cardiac compression. Obtain medical attention.

Advice to Doctor: Treat symptomatically. Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

Exposure Limits: Recommended 80 ppm, 8 hour Time Weighted Average.

Engineering Controls: Exposure to this material may be controlled in a number of ways. The measures appropriate for a particular worksite depend on how the material is used and on the potential for exposure. Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions. If



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ENAMEL THINNERS F59-180

Page 3 of 4

engineering controls and work practices are not effective in preventing or controlling exposure, then suitable personal protective equipment, which is known to perform satisfactorily, should be used.

Personal Protection: Ensure a high level of personal hygiene is maintained when using this product. Wash hands before eating, drinking or using the toilet. Wear chemical goggles. Wear chemical resistant gloves. Wear protective clothing as necessary to avoid skin contact. Wear respiratory protection if there is a risk of exposure to high vapour concentrations which meet the requirements of AS/NZS1715 and AS/NZS1716.

Flammability: Avoid heat and sources of ignition. Prevent build-up of flammable vapours. Hoses should be electrically continuous and containers bonded to avoid static charge build-up.

SAFE HANDLING INFORMATION

Storage and Transport: Store in cool well ventilated area away from heat and ignition sources. Containers should always be kept closed in storage and properly labelled. Do not store in low or enclosed areas where vapours may become trapped. Store only in original or approved containers and do not re-use empty containers without proper cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures. Classified as a class 3 Flammable Liquid for the purpose of transport. The product is a scheduled Poison (S5) and must therefore be stored, maintained and used in accordance with the relevant State Poisons Act.

Spills and Disposal: Keep public away. Extinguish all ignition sources. For major spills, dam and recover. Prevent entry into drainage systems, rivers etc. Collect with absorbent material such as sand, earth or saw dust. Warn occupants downwind. Advise authorities. Ensure waste disposal conforms with local waste disposal regulations. After recovery and evaporation remaining soil may be disposed of to approved landfill, or if approved, allowed to degrade insitu.

Fire/Explosion Hazard: Flammable liquid. Combustion products include oxides of carbon. Use water sprays to cool fire exposed surfaces and any adjacent storage vessels. Shut off source of product if safe to do so. Remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along vapour trail may occur. Avoid contact with strong oxidizing agents and strong caustics. Use foam, CO₂, dry chemical and water fog. Wear full protective clothing and self-contained breathing apparatus.



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ENAMEL THINNERS F59-180

Page 4 of 4

Other Information:

Toxicology

Oral LD50 (rat) Practically non-toxic >2000mg/kg. Inhalation LC50 (rat) Practically non-toxic. Dermal LD50 (rabbit) Practically non-toxic >2000mg/kg.

Prolonged or repeated skin contact may defat the skin resulting in possible irritation and dermatitis.

RISK PHRASES:

R10: Flammable.

R65: May cause lung damage if swallowed.

SAFETY PHRASES:

S2: Keep out of reach of children.

S16: Keep away from sources of ignition - No Smoking

S24: Avoid contact with skin.

S33: Take precautionary measures against static discharges.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Contact Point: Technical Director (02) 9603-3399

Date: March 2009