



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ISOPROPANOL FSU12

Page 1 of 5

MATERIAL SAFETY DATA SHEET

Not classified as hazardous according to criteria of Worksafe Australia.

Date of issue: March 2009

COMPANY DETAILS

AUSTRALIAN SPECIALTY INKS PTY LTD

A.B.N. 71 002 591 620

17 REAGHS FARM ROAD MINTO NSW

2566(02) 9603-3399

A/H (02) 979-27790 or mobile 0414 616247

IDENTIFICATION

Product Name: ISOPROPANOL FSU12

U.N. Number: 1219

Trade Name:

Other Names: PROPAN-2-OL, PROPYL ALCOHOL

Dangerous Goods Class/and Subsidiary Risk: 3

Hazchem Code: 2[Y]E

Manufacturers Code: FSU12

Poisons Schedule: Not scheduled

Pack Group: II

Use: Product is for use as a solvent

PHYSICAL DATA

Appearance Clear liquid with characteristic odour.

Melting Point -88°C

Boiling Point 82-83°C

Vapor Pressure 4.17 Pa @ 20°C

Specific Gravity 0.78-0.79 at 20°C

Flash Point 12°C (Abel)

Flamm. Limit LEL LEL: 2% UEL: 12%

Other Properties

Autoignition Temp. 425°C

Vapor Density 2 (Air = 1) at 20°C

Other Information Evaporation, Rate: 1.5 (referenced as n-butyl acetate = 1)

Solubility inWater Completely miscible

Ingredients

Name	CAS	Proportion
Isopropanol	67-63-0	98-100%



HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Acute - Ingestion Swallowing may have the following effects: irritation of mouth, throat and digestive tract. A large dose may have the following effects: headache, muscular weakness, drowsiness.

Acute - Eye Liquid will irritate.

Acute-Skin Not irritating to the skin. Repeated or prolonged contact may produce defatting of the skin leading to dermatitis.

Acute - Inhalation Inhalation of vapours or mists may cause irritation to the respiratory system. A large dose may have the following effects: headache, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

FIRST AID

Ingestion Wash out mouth with water. Do not induce vomiting. Keep warm and at rest. If there is difficulty in breathing, give oxygen. If breathing stops or shows signs of failing, apply artificial respiration. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Obtain medical attention.

Eye Immediately flood the eye with plenty of water, preferably warm, for at least 15 minutes, holding the eye open. Obtain medical attention urgently.

Skin Wash skin with soap and water. Continue washing for at least 15 minutes. Contaminated clothing should be washed or dry-cleaned before re-use.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing, give oxygen. If breathing stops or shows signs of failing, give artificial respiration. Obtain medical attention.

Advice to Doctor Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation. Causes central nervous system depression.

PRECAUTIONS FOR USE

Exposure Limits	Name	STEL m/m3 ppm	TWA m/m3 ppm	TWA Footnote
	Isopropanol	500	400	



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ISOPROPANOL FSU12

Page 3 of 5

Other Exposure Info. Engineering Controls: As published by the National Occupational Health and Safety Commission (Worksafe Australia). Exposure to this material may be controlled in a number of ways. The measures appropriate for a particular worksite depend on how the material is used and on the potential for exposure. Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions. If engineering controls and work practices are not effective in preventing or controlling exposure, then suitable personal protective equipment, which is known to perform satisfactorily, should be used.

Protective Equipment **RESPIRATORY PROTECTION:** Respiratory protection if there is a risk of exposure to high vapour concentrations. **HAND PROTECTION:** Butyl rubber gloves. Full length gloves must be worn during all handling operations. **EYE PROTECTION:** Chemical goggles or face shield. **BODY PROTECTION:** Normal work wear.

Fire Hazards: A highly flammable liquid. Avoid heat and sources of ignition. Prevent build-up of flammable vapours. Hoses should be electrically continuous and containers bonded to avoid static charge build-up.

SAFE HANDLING INFORMATION

Storage and Transport:

Storage area should be cool, well ventilated. Store away from sources of heat or ignition. Storage and transfer equipment should be adequately earthed and bonded to prevent the accumulation of static charges. Storage tanks must be positioned within a bonded area. Suitable storage materials are: mild steel, stainless steel, aluminium and its alloys, copper and its alloys. Do not store in certain plastics. For gaskets and seals butyl rubber, PTFE.

Ship. Name (CSN) ISOPROPANOL

Other Storage Info. **HANDLING:** Use in well ventilated area. Avoid inhaling vapour. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use.

Spills and Disposal:

ACCIDENTAL RELEASE MEASURES: **PERSONAL PRECAUTIONS:** Wear appropriate protective clothing. Consider need for evacuation. Eliminate all sources of ignition. Beware of vapours accumulating to form explosive concentrations.

ENVIRONMENTAL PRECAUTIONS: Try to prevent the material from entering drains or water courses. Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation. Prevent spread of material by use of temporary bund or impervious barrier. **SPILLAGES:** Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal. Finally flush area with plenty of water.

DISPOSAL: **PRODUCT DISPOSAL:** Incineration. Dispose of in accordance with all applicable local and national regulations. Use an approved disposal company.

CONTAINER DISPOSAL: Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld or near to the container. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate.



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ISOPROPANOL FSU12

Page 4 of 5

Fire/Explosion Hazards

EXTINGUISHING MEDIA: Use alcohol-resistant foam, dry chemical or carbon dioxide. Water spray to cool containers. **UNSUITABLE EXTINGUISHING MEDIA:** Do not use water jet. **SPECIAL HAZARDS OF PRODUCT:** Containers may explode in heat of fire. Vapours can travel a considerable distance to a source of ignition and flashback. Moderate to severe explosion hazard in confined spaces. Run off to sewer may cause fire or explosion hazard. **PROTECTIVE EQUIPMENT FOR FIREFIGHTING:** Wear full protective clothing and self-contained breathing apparatus.

Hazardous Reaction

STABILITY: Stable under normal conditions. **CONDITIONS TO AVOID:** High temperatures. Static discharge. **MATERIALS TO AVOID:** Strong oxidising agents. Strong mineral acids. **HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion will generate oxides of carbon, acrid smoke and irritating fumes.

Other Information:

Toxicology

ACUTE TOXICITY: Low order of acute toxicity Dermal LD50 (rabbit) 2000 mg/kg. Oral LD50 (rat) 2000 mg/kg.

IRRITANCY - EYES: The product is an eye and respiratory irritant.

SKIN SENSITISATION: Studies have not revealed any evidence of skin sensitisation effects.

REPRODUCTIVE/DEVELOPMENTAL TOXICITY: Developmental effects have been observed in laboratory animals. Experimental studies in animals have provided some evidence of embryo/foetotoxicity and birth defects only at doses producing mild maternal toxicity.

Environ. Protection

MOBILITY: The product will dissolve in water. The product is volatile/gaseous and will partition to the air phase.

PERSISTENCE/DEGRADABILITY: Readily biodegradable meeting the 10 day window criterion. Photochemical degradation in air will be fast. \

BIO-ACCUMULATION: Product is not expected to bioaccumulate significantly.

ECOTOXICITY: Fish Low Toxicity: LC/EC/1150 > 100 mg/l

Packaging & Labelling

HAZARD CATEGORY: IRRITANT, HIGHLY FLAMMABLE.



Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: www.austspecialtyinks.com.au

ISOPROPANOL FSU12

Page 5 of 5

RISK PHRASES:

R11: Highly flammable.

R36/37: Irritating to eyes and respiratory system.

R67: Vapours may cause drowsiness or dizziness

SAFETY PHRASES:

S2: Keep out of reach of children

S9: Keep container in a well ventilated place.

S16: Keep away from sources of ignition - No Smoking

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Contact Point: Technical Director (02) 9603-3399

Date: March 2009