

Australian Specialty Inks Pty Ltd

17 Reaghs Farm Rd, Minto NSW 2566 Telephone: (02) 9603-3399 Fax: (02) 9603-7761 Website: www.austspecialtyinks.com.au

PRODUCT INFORMATION

HYDROPACK

Main Characteristics

Finish	Drying	Thinner Wash up	Mesh	Stencil	Coverage	Application	Colour Range
Semi Gloss	Jet dry in seconds, touch dry approximately 5 minutes.	Water	Mono Filament fabric 62t to 100t.	Any water resistant or duel cure emulsion.	Depending on mesh count used, approximately 40 sq mt per lt	Paper and boards.	20 Standard colours, plus Black and White. Special colours as required

PRODUCT DESCRIPTION:

Hydropack is a water reducible and water wash up system specifically developed to cover the needs of the printer who requires an ink to be totally solvent free and suitable for a wide range of papers and boards. The inks have a wide range of acceptance and are ideally suited for the commercial printer, art student or the hobbyist.

The inks may be printed by hand or by machine operation, finished prints display a semi gloss finish with good scuff resistance along with a positive bond to most papers and screen boards.

Hydropack inks are **NOT intended for the printing of fabrics or industrial grade materials such as vinyl's, metals,** treated or untreated polyethylene or polypropylene or like materials.

Thinners

Hydropack inks are designed to be used straight from the container, however up to 10% water can be added if required. The drying time of the inks can be slowed by the addition of up to 10% Hydropack Retarder Thinner HP182.

Care should be taken not to use excessive amounts of Thinner or Retarder as excessive reduction can have an adverse effect on the overall finished print quality.

It is recommended that the Hydropack MSDS be consulted before using this product.